

THUNDERVOLT® AGM BATTERIES



FEATURES:

- Patented post design reduces internal battery resistance by replacing 3 internal connections with 1.
- Flush mount, threaded terminals allow for easy connection to bike terminals.
- Nonspillable, sealed AGM Valve Regulated Lead Acid (VRLA) design is maintenance free and meets all requirements for shipment via air carrier.
- Rugged construction has been lab tested and field tested to ensure long life, even in demanding V-Twin applications.
- Higher AH capacity than OEM means more starting capacity before wearing battery down, particularly useful for those stubborn steeds.
- Manufactured by an ISO 9001:2000 registered factory
- Patented Cast-On-Stip (COS) manufacturing technology ensures consistent long battery life.

Ultima® Part No.	OEM Part No.	CCA	Applications
1-140	65989-97B	310	Softail® 1997/later, XL 1997/2003, Dyna® 1997/later, VROD (except VRSCR) 2007/later
1-141	66007-84	280	FL & FLH models 1965/1984. Sportster® models electric start 1967/1978, except XLCR.
1-142	66010-97B	385	FLH, FLT 1997/later
1-143	65958-04	200	XL models 2004
1-144	65989-90B	240	Dyna® & Softail® models 1991/1996
1-145	65991-82B	240	Electric start FX and FXR 1973/1994; XLCR 1977/1978, XL models 1979/1996; Softail® models 1984/1990; FXR models 1999/2000
1-146	66010-82B	350	FLHR, FLHT, and FLT Touring models 1980/1996
1-147	65948-00	200	VRSC models 2002/2006, VRSCR 2007
1-148	66006-70		FX & XL models (kickstart only) 1970/1978.

Ultima®'s AGM Thundervolt® batteries are the highest performance batteries we offer today! These are an industry first, with a direct fit aftermarket replacement for OEM# 65989-97A. These batteries provide some of the highest power ratings available in the Aftermarket.

1-150 V-Twin Terminals. Replacement terminals & screw for above battery. Except **1-148** & **1-141**.

Maintenance-free 20 amp hour, 12V for custom applications.

1-110	--	230	Custom. 6" L x 3-7/16" W x 4-3/8" H
1-117	--	230	Custom. YTX16-BS. 6" L x 3.4375" W x 6.375" H

PART NO.	YUASA EQUIVALENT	OEM NO.	AH	CCA	LENGTH	WIDTH	HEIGHT
1-140	YTX20L-BS	65989-97B	18	310	7.000	3.500	6.125
1-141	YHD-12	66007-84	28	280	8.125	5.125	6.500
1-142	Y1X30L	66010-97B	30	385	6.750	5.250	7.000
1-143	YTX14L-BS	65958-04	12	200	6.000	3.500	5.750
1-144	YTX20L-BS (YB16L-B)	65989-90B	19	240	7.000	4.000	6.250
1-145	YTX20-BS (YB16-B)	65991-82B	19	240	7.000	4.000	6.250
1-146	YTX24HL-BS	66010-82B	22	350	8.125	3.750	6.500
1-147	YTX14-BS	65948-00	12	200	6.000	3.500	5.750
1-148		66006-70					

